

USB DRIVER RELEASE NOTES

V3.20 Driver – up to Windows 10

For devices with attached USB Card V1.05 or V1.1 only. *For devices not listed here, see V1.61 Driver.*

1. Factory fitted **after 03. 03. 2016** into the devices listed below:
 - Thesis Alpha, SN: from 812010018- (230V), 811010005- (120V)
 - Obelisk DA, SN: from 742030098- (230V), 741010015- (120V)
 - Dactilus 3, SN: from 723030138-
2. Factory or Dealer fitted USB Card V1.05 or V1.1 into the devices listed below:
 - Canalot

Supported sampling frequencies (USB Card V1.05 and V1.1):

- 44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz

V1.61 Driver – up to Windows 10*

For devices with attached USB Card V1.0.

1. Factory fitted **before 03. 03. 2016** into the devices listed below:
 - Thesis Alpha, SN: to -812010017 (230V), -811010004 (120V)
 - Obelisk DA, SN: to -742030097 (230V), -741010014 (120V)
 - Dactilus 3, SN: to -723030137
2. Factory or Dealer fitted USB Card V1.0 into the devices listed below:
 - Canalot

Supported sampling frequencies (USB Card V1.0):

- 44.1 / 48 / 88.2 / 96 / 192 kHz

**- requires disabled driver signature enforcement*

Notes:

1. From 01. 05. 2016 it is possible to upgrade USB Card from Rev. 1.0 to Rev. 1.1.
2. USB Card version visual determination:
 - USB Card V1.0 marked with „Rev 1.0” sign and yellow round mark on the back of the card
 - USB Card V1.05 marked with „Rev 1.0” sign and white rectangle mark on the back of the card
 - USB Card V1.1 marked with „Rev 1.1” sign and white rectangle mark on the back of the card